



Instructions for Part 45-1205B Windshield Garnish Vent Light

NOTE: Read instruction carefully before installation

Caution: Disconnect the battery ground prior to connecting wires.

1. Remove windshield garnish in accordance with the service manual.
2. Place windshield garnish on a clean soft surface painted side down. **Fig. 1**
3. Clean windshield garnish around vent holes with alcohol prep swab.
4. Clean vent light with alcohol prep swab.
5. Apply the two sided tape along the windshield garnish vent as shown in **Fig. 1**
6. Apply the flexible windshield garnish vent light to the two sided tape, as shown in **Fig. 2** and press down for one minute.




Figure 1



Figure 2

Wiring:

Red wire - Positive
Clear wire - Ground

1. Attach the red wire from the flex light to the running light wire going to the front running light inside the mirror assembly with the quick wire tap provided.

Left side mirror power wire-Orange/White
Right side mirror power wire-Blue/White

2. Attach the clear ground wire from the flex light to the windshield garnish mounting bolt with the ring terminal provided.

3. Test light.

4. Reinstall windshield garnish in accordance with the service manual.





Instructions for part 45-1205B Front Fender Garnish Light

NOTE: Read instructions carefully before installation.

CAUTION: Disconnect the battery ground prior to connecting the wires.

1. Remove windshield garnish in accordance with the service manual.
2. Remove front fender garnish in accordance with the service manual.
3. Clean front fender garnish with alcohol prep swab.
4. Clean light with alcohol prep swab.
5. Apply two sided tape to the front fender garnish as shown in **Fig. 1**
6. Apply the flexible light to the two sided tape, as shown in **Fig. 2**, and press down for one minute.



Wiring:

Red wire - Positive
Clear wire - Ground

1. Attach the red wire from the flexible light to the running light wire going to the front running light inside the mirror assembly with the quick wire tap provided.

Left side mirror power wire-Orange/White
Right side mirror power wire-Blue/White

2. Attach the clear ground wire from the flexible light to the windshield garnish mounting bolt with the ring terminal provided.

3. Test light.

4. Reinstall front fender garnish in accordance with the service manual.

5. Reinstall windshield garnish in accordance with the service manual.

