



Installation Instructions

XtraSlim LED Strip Lights

SGULST19AM - Amber
SGULST19GR - Green
SGULST19NB - Blue

SGULST19PR - Purple
SGULST19RD - Red
SGULST19WH - White

Note: Unique right angle mounted LED's focus light at a 90° angle. Check lights before permanent mounting.

Step 1: Surface Prep

All mounting surfaces must be clean and free of dirt, wax, and oil prior to the installation. Wipe all surface areas with alcohol prep pad provided and let dry thoroughly before installing LED strip.

Step 2: Trim to fit

LED stripes can be cut to desired lengths in increments of three LEDs each. There are "cut marks" indicated on the strips indicating where to make the cut without damaging the strip. The strip can be cut at a cut mark using a pair of scissors. After making the cut to the strip, the cut end must be sealed with epoxy, a silicone sealer or electrical tape so there will be a weather tight seal.

Step 3: Installation Instructions

Choose a desired location to mount the LED strip. Simple peel and stick application. Install on flat smooth surfaces such as fairing, head light housing, instrument panels, etc. Mount the LED strip in the desired location by removing the adhesive backing from the strip, position strip in desired location, press firmly to mounting surface and hold for 30 seconds.

NOTE: The trimmed L.E.D. strip end is recommended to be sealed with a waterproof sealer or electrical tape.

Wiring Connections: Making connections of power and ground wires.

*Black wire with white strip 12v battery (+) power source

*Black wire Negative (-) ground